



# E09 Power Box

## LED Power Box

### FEATURES

- Universal AC input (100-264V AC)
- Galvanized Steel Enclosure w/ Knockouts
- Simple Wiring
- Cooling by Free Air Convection

### MODELS

- 25 Watts
- 45 Watts

### ENVIRONMENT

- Dry
- Damp

## ELECTRICAL SPECIFICATIONS

MODEL	PS24V45W-E09	PS09V25W-E09
Continuous Output Power <sup>1</sup>	45 Watts	25 Watts
Maximum Output Power	60 Watts	30 Watts
Output Voltage	24V DC, Constant Voltage	9.1V DC, Constant Voltage
Output Current	2.5A	3.3A
Input Voltage	100-264V AC	90-264V AC
Input Frequency	50/60 Hz	50/60 Hz
Input Current	1.2A/115VAC	<1.5A RMS Max.
Operating Temp. Range <sup>2</sup>	-30° to 40°C	0°C to 30°C
Environment	Dry, Damp	Dry, Damp
Certification	cULus (US & Canada)	cULus (US & Canada)

<sup>1</sup> Specified wattage is derated and is the maximum recommended load under normal operating conditions. Provided the Power Box is operated within the specified operating temperature range, additional derating is not required.

<sup>2</sup> Operating Temp. Range is contingent on the Power Box being installed in free air.

## MECHANICAL SPECIFICATIONS

