


Gen5™ Demarcation

LED LINEAR LUMINAIRE

The Gen5 Demarcation is an escalator-grade LED luminaire designed for the bright, clear and long-lasting demarcation. Each light comes with an integrated 6 foot cable.



FEATURES

Incredibly Bright

Our vibrant green LEDs can last 50,000 hours or more.

Integrated Cable

Convenient 6 foot cable with each fixture simplifies installation.

Simple Power

AC Power Supply can power up to four 18" Gen5 Demarcation fixtures with outstanding performance.

Rugged Design

Impact-resistant polycarbonate optic and anodized aluminum construction ensure product longevity.

Snap-In Mounting

Adjustable and fixed-mount brackets make mounting simple.



Typical Applications

- Escalator Demarcation

Quick Specs

9W	Power
180	Lumen Output / Foot Typ
65°	Beam Angle

LED Color

Vibrant Green

Housing

Black Mil-Spec Anodized Aluminum

Mounting

Adjustable & Fixed Mounts

Gen5™ Demarcation

MODEL S1203 | LED LINEAR ESCALATOR DEMARCATION LUMINAIRE

The Gen5 Demarcation is an escalator-grade LED luminaire designed for the bright, clear and long-lasting demarcation. Each light comes with an integrated 6 foot cable.



CUSTOMER COMPANY

CUSTOMER CONTACT

P.O. #

CUSTOMER PHONE #

NEED-BY DATE

ONCE COMPLETE SEND TO

FIXTURE BUILDER

S1203	A	-	8	6	D	
-------	---	---	---	---	---	--

FIXTURE TYPE

Gen5 Demarcation

OUTPUT

A 9 Watts

LENGTH

8 18"

BEAM ANGLE

6 65°

LED COLOR

D Vibrant Green

NUMBER OF KITS

Specific quantity of demarcation kits for this order.

NUMBER OF POWER SUPPLIES

(OPTIONAL) Specific quantity of power supplies for this order.

ACCESSORIES

POWER SUPPLY (OPTIONAL)

	VOLTAGE	POWERS
<input type="checkbox"/>	PS24V60W-01	120-240V AC 4 Fixtures

Use 1 Power Supply for up to 4 Gen5 Demarcation fixtures. Alternatively, use your own 9-30V DC Power Source.

BRACKETS


BRACKETS	
<input type="checkbox"/>	SLA-1 Adjustable
<input type="checkbox"/>	SLA-2 Fixed

Use 2 brackets per Gen5 Demarcation fixture.

QUICK SPECS

Input Voltage	9-30V DC	Max. Lights per Power Supply	4 Lights
Power	9 Watts	Wiring	6 foot cable
Operating Temp	-20°C to 40°C	Housing	Mil-Spec Anodized Aluminum
Max. Case Temp	50°C	Lens	Impact Resistant Polycarbonate
Humidity	0 to 95% Non Condensing		

18.42" [468mm]



PRODUCT EXAMPLE

