

When used with SlimFit Case Fixture.

# E09SC Power Box

## LED Power Box for SlimFit™ Case


### FEATURES

- Molded 120V AC Power Cable
- Galvanized Steel Enclosure
- Simple Wiring
- Cooling by Free Air Convection

### MODELS

- 45 Watts

### ENVIRONMENT

-  Dry
-  Damp

## ELECTRICAL SPECIFICATIONS

MODEL	PS24V45W-E09SC
Continuous Output Power <sup>1</sup>	45 Watts
Maximum Output Power	60 Watts
Output Voltage	24V DC, Constant Voltage
Output Current	2.5A
Input Voltage	100-132V AC
Input Frequency	50/60 Hz
Input Current	1.2A/115VAC
Operating Temp. Range <sup>2</sup>	-30° to 40°C
Environment	Dry, Damp
Certification	cULus (US & Canada) <sup>3</sup>

<sup>1</sup> Specified wattage is derated and is the maximum recommended load under normal operating conditions. Provided the Power Box is operated within the specified operating temperature range, additional derating is not required.

<sup>2</sup> Operating Temp. Range is contingent on the Power Box being installed in free air.

<sup>3</sup> UL Listing is contingent on the Power Box's use with i2Systems SlimFit Case LED Fixture.

## MECHANICAL SPECIFICATIONS

